

CURV-RITE ALUMINUM EDGING 3603 NORTH MAIN ST. WAYLAND, MICHIGAN 49348 TOLL FREE: 1-800-366-2878 PHONE: (269) 792-0044

FAX: (269) 792-8126 www.curv-rite.com

TECHNICAL SPECIFICATION:
LANDSCAPE BE EDGING SHALL BE CURV-RITE:
(THICKNESS) INCH THICK ALUMINUM EDGING, (DEPTH)
INCHES DEEP WITH A (FINISH) AS MANUFACTURED BY
CURV-RITE, INC. WAYLAND, MI: 1-8000-366-2878. SIXTEEN
(16) FOOT SECTIONS SHALL BE USED WITH (1)
SUBSURFACE STAKE PER (38) INCHES OF EDGING.
EDGING SHALL HAVE A MINIMUM OF (2) INCHES OF
INTERLOCKING OVERLAP BETWEEN SECTIONS. INSTALL
PER MANUFACTURER'S SPECIFICATIONS WITH TOP OF
EDGING 1/4" TO 1/2" ABOVE COMPACTED FINISH GRADE.
FINISH GRADE TO BE COMPACTED ON EITHER SIDE OF
EDGING TO MAINTAIN STABILITY.

THICKNESS DEPTH LENGTH

(3.2MM X 76MM X 203.2MM)

(3.2MM X 102MM X 203.2MM)

(3.2MM X 102MM X 406MM)

(3.2MM X 140MM X 406MM)

(4MM X 102MM X 406MM)

(4MM X 140MM X 406MM)

1/8" X 3" X 8'


1/8" X 4" X 8'

1/8" X 4" X 16'

1/8" X 5.5" X 16'

3/16" X 4" X 16'

3/16" X 5.5" X 16'



* DECO-BRONZE AND DECO-GREEN IN THIS SIZE REQUIRE A MIN. PURCHASE OF 2400'

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWINGS.
- 3. CONNECTION BETWEEN STRIPS TO UTILIZE MANUFACTURER'S UNIQUE INTERLOCKING SPLICER.
- CONTRACTORS NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info REFERENCE NUMBER 078-003.



078-003