

4000™ Series



HEAVY DUTY ALUMINUM EDGE RESTRAINTS



For Keeping and Defining . . .



DG Pathways



Cut Natural Stone



6cm+ Pavers



Thin Pavers

4000 Series™ is engineered to offer a durable edge for high traffic areas. Specifically designed to permanently keep natural stone and/or manufactured pavers/slabs in place.

Ideal Restraint For:



Bluestone



decomposed granite



Pavers



loose aggregate



paving slabs

... In Addition to ...

- Belgian Block
- Cobblestone
- Permeable Pavers
- Flagstone
- Asphalt Pavers
- Compacted Aggregate

Features ... Benefits

Different heights available ... to match different stone thicknesses.
Heavy wall thickness ... increased strength for heavy-duty applications.
Wider flange ... larger footprint increases product performance.
Available in Rigid ... for perfect straight lines.
Available in Flexible ... for curvilinear applications.

Available Sizes:

- 1"H x 2"W x 8 ft. Long
- 1.5"H x 2"W x 8 ft. Long
- 2"H x 2"W x 8 ft. Long
- 2.5"H x 2"W x 8 ft. Long
- 3"H x 3"W x 8 ft. Long
- 4"H x 3"W x 8 ft. Long

Available Finishes:

- Mill Finish
(natural aluminum)
- Deco-Black
(electro-statically applied paint)

Curv-Rite, Inc.
Wayland, MI USA
800-366-2878
www.curv-rite.com

CURV-RITE® PRODUCTS: TECHNICAL SPECIFICATIONS

Technical Specifications for:

Curv-Rite 4000 Series Heavy Duty “L” Shaped Aluminum Edge Restraint

Edge Restraint to be **Curv-Rite 4000 Series Heavy Duty “L” Shaped Aluminum Edge Restraint: (size)** with a **(finish)** in an 8' section as manufactured by Curv-Rite, Inc.; Wayland, MI. 1-800-366-2878. Sections to be aluminum alloy 6061 with a T-6 hardness. A 3" aluminum splicer inserted 1-1/2" into each adjoining section shall be used to create an uninterrupted edging system that has a continuous support surface on both sides of the vertical wall. Edging base shall have holes 4" apart along its length of section for receiving 3/8" x 10" steel spikes. **(Specify qty. of spikes per section-up to 25 max)** spikes shall be used per 8-ft. section.

Size:

- 1" (25mm) high x 2" (51mm) base.
- 1.5" (38mm) high x 2" (51mm) base.
- 2" (51mm) high x 2" (51mm) base.
- 2.5" (64mm) high x 2" (51mm) base.
- 3" (76mm) high x 3" (76mm) base.
- 4" (102mm) high by 3" (76mm) base.

Finish:

Natural Aluminum Finish (Mill)
Deco-Black Finish (.0008 to .0012 inch thick) Electrostatic Enamel Acrylic