



*Breathable Membranes for Rainscreen Wall and Sloped Roof Systems*

## SRP-Eternabond 1" D.S. "Double Stick" Seam Tape

### **Basic Use**

This self sealing adhesive creates a water tight, conformable seal between layers of SRP Roofshield, SRP Wallshield, SRP AirOutshield, SRP AirOutshield ROOF and at junctions with other materials.

### **Composition**

DoubleStick Tape utilizes EternaBond's advanced MicroSealant™ Technology, a 100% solids formulation of synthetic resins, thermoplastics, non-curing rubbers (not butyl), with a built in primer, sandwiched between two siliconized release liners.

### **Technical Data**

Standard roll sizes 1" X 50'  
Total thickness standard is 30mils  
Adhesion 19lbs/in width  
Low temp flexibility Excellent  
Application temp. range -25°F - > 150°F  
Temperature range -70°F - >200°F  
Pliability No cracks in membrane  
Water vapor test (ASTME 96B) .005 grms/100" sq./24hrs/100°F  
Permanence .001 perms maximum  
Elongation >500%  
Shelf life Up to 5 years

### **Surface Preparation**

Surface must be clean and dry. Moisture, dust, dirt, and other foreign matter should be removed. Remove oil, grease, and etc. with a suitable cleaner.

### **Application**

To apply the DoubleStick, remove the release liner on one side of the DoubleStick and apply to the surface to be bonded. Remove the 2nd release liner, apply pressure using a small seam roller or similar to fully bond tape to the surfaces.

---

**SRP Canada Inc.**

[www.srpcanada.ca](http://www.srpcanada.ca)

1-866-533-0233

Updated 2009-04-01